

## TILE CREAM

HONING CREAM FOR CORROSIONS/ABRASIONS ON PORCELAIN STONEWARE AND CERAMIC

### DESCRIPTION

TILE CREAM is a water based, honing cream. Specific for the restoration of ceramic and porcelain stoneware materials where normally particular machinery, long hours and water are required. Product renews dull and consumed surfaces, scratches and abrasions. Application unifies and sharpens surface aspect, while increasing surface gloss matching results obtained by traditional diamond honing in only a few passes. Product works chemically and mechanically by reacting with the material hardening the natural structure of the stone, closing the surface pores therefore increasing resistance to general foot traffic and surface dirt.



### CAN BE APPLIED WITH



FLOOR MACHINE 150/175 RPM AND  
ORBITAL WHEEL

### ADVANTAGES

- Fast & effective
- Economical
- High gloss
- Durable

### WHERE TO APPLY

For internal/external ceramic and porcelain stoneware.

### USE

Test on a small area before proceeding, so to ensure product suitability and final result. Apply product to small workable areas at a time. (approx. 2 sqm). Remove all surface debris and previous applied waxes or top coats before applying product. Shake container before use.

Apply product over the area to be treated and add water so to maintain a creamy/pasty mixture. Proceed to buff surface (175 rpm) using a white nylon pad, making sure that the mixture does not dry out. If necessary add water to the mixture. Check gloss regularly and continue until desired gloss is obtained.

Remove all product residue with clean water and squeegee or wet vacuum. Rinse surface.

Note: on extreme honed or consumed surfaces, apply 20/30 gr. of product per sqm and buff with at least 20 passes.

Maintenance: on material with extreme foot traffic, maintain surface with 10/20 gr. of product per sqm and buff with at least 15 passes. For traditional spray buffing maintenance proceed to use "Neutral Crystallizer" as directed.

### TECHNICAL DATA

ASPECT	: CREAM
COLOUR - ODOUR	: WHITE - ODOURLESS
PH (5% IN WATER)	: 7 -8
SPECIFIC GRAVITY (20°)	: NR
BIODEGRADABILITY	
FLASH POINT	: NOT FLAMMABLE

### COVERAGE

40-50 SQM/KG

### PRE-CAUTIONS

DO NOT ALLOW THE PRODUCT TO DRY DURING POLISHING PHASE .

### SAFETY

THE PRODUCT IS NOT SUBJECT TO CLASSIFICATION FOLLOWING THE LAWS IN FORCE .  
S2-KEEP OUT OF THE REACH OF CHILDREN  
S24/25-AVOID CONTACT WITH EYES AND SKIN  
S37- WEAR SUITABLE GLOVES

STORAGE : KEEP THE CONTAINER CLOSED AND IN A COOL PLACE .

SHELF LIFE : 24 MONTHS IN THE ORIGINAL SEALED PACKING AND KEPT IN A COOL AND DRY PLACE .

PACKAGING : 5 KG CAN (4 CANS PER CARTON )

THOUGH THE INFORMATION ON THIS SHEET ARE THE RESULTS BOTH OF OUR RESEARCH AND OPERATIONAL TECHNICAL EXPERIENCE, THEY CANNOT BE CONSIDERED UNDERTAKING OR INVOLVE OUR RESPONSIBILITY AS THE CONDITIONS REQUIRED FOR THE APPLICATION CANNOT BE SUPERVISED BY US. FABER CHIMICA S.R.L. DOES NOT PROVIDE ANY WARRANTY, EITHER EXPRESS OR IMPLIED AND DOES NOT ASSUME ANY RESPONSIBILITY CONCERNING THE USE OF THESE DATA AND SUGGESTIONS.